

OMNI print i n c .

Product Features

- THERMAL LINE PRINTING
- 200 X 200 DPI RESOLUTION
- 15 LPS PRINTING SPEED
- USER FRIENDLY
- AUTO PAPER LOADING
- LABEL GAP SENSOR
- BAR CODE
- GRAPHICS
- LABEL DESIGN SOFTWARE



OM-L60

Applications

- TICKET
- MEDICAL
- BAR CODE
- COUPON
- TEST & MEASUREMENT

AFFORDABLE BAR CODE LABEL PRINTER WITH WYSIWYG LABEL DESIGN.

OM-L60

OmniPrint i n c .

MODEL	OM-L60
PRINTING METHOD	THERMAL LINE PRINTING
DOT DENSITY	203 DPI x 203 DPI
PRINTING WIDTH	56 mm, 448 DOTS
NO. OF COLUMNS	32
FONT SIZE	12 x 24
LINE SPACING	1/6 INCH DEFAULT, PROGRAMMABLE
PRINT SPEED	15 LINES/SEC OR 50 mm/s
PAPER	Media THERMAL LABEL, 0.2 mm MAX Label DIE CUT, 60 mm (W) MAX, 20 - 120 mm (L) Roll 90 mm DIA. MAX, 25 mm ID CORE
DATA BUFFER	1K BYTE
INTERFACE	RS232C SERIAL
SOFTWARE	QUICK-LABEL, WYSIWIG LABEL DESIGN
POWER SUPPLY	Input 90-265 VAC 50/60Hz (EXTERNAL) Output 24VDC, 1.5A
ENVIRONMENTAL	5 - 45 °C AND 30 - 80 %RH (OPERATING) -15 - 50 °C AND 10 - 90 %RH (STORAGE)
RELIABILITY	Mech 10 MILLION LINES Head 50 MILLION PULSES, 50Km
DIMENSIONS (mm)	100 (W) x 205 (D) x 130 (H)
WEIGHT	1.4 lbs
SAFETY STANDARDS	FCC, CE, UL, cUL



OM-L60-CS



OM8300



STP100



TP-L60

External Dimensions



OMNIPrint, Inc.
14 Chrysler, Irvine, CA 92618, USA
Telephone : (949) 457-0229
Fax : (949) 457-9016
www.omniprintinc.com

